

AGRIFLEX+ 372

HEAVY DUTY TIRES FOR HIGH PERFORMANCE TRACTORS AND COMBINES.



- Engineered with increased flexion and very increased flexion (IF/VF) technology
- High speed capabilities, both on and off road
- Provides up to 40% more load capacity than standard tires for higher productivity
- Allows up to a 40% decrease in tire pressure compared to standard tires, preventing soil compaction and field damage
- Steel-belted tread for puncture resistance
- Stubble guard compound for long tread life
- Unique multi-angled tread design to ensure long life and a smooth ride, on the road or in the field



**LARGE FOOTPRINT, LOW SOIL COMPACTION, GREAT TRACTION.
INCREASED PRODUCTIVITY AND REDUCED COSTS.**

PREMIUM TECHNOLOGY, EVERYDAY AFFORDABILITY.

AGRIFLEX+ 372




TRACTOR



COMBINE HARVESTER

MINIMIZE SOIL COMPACTION



STEEL BELTED




HIGH SPEED CAPABILITIES BOTH ON AND OFF-ROAD



Product Code	Size	Load Index	NS (32 nd)	RIM	Overall Diameter	Section Width	Rolling Circ.	Speed (MPH)	Max Load
37200020AL	IF520/80R26 CFO	165A8	57	DW16	57.7	19.9	172.1	30	11350
37200080AL	VF620/70R26	170D	57	DW21B	58.5	24.6	172.7	40	13220
37200008AL	VF420/85R28 CFO	151D	58	DW15	56.6	17.6	167.8	40	7600
37200048AL	VF600/60R28	146D	62	DW20B	61.4	24.6	163.7	40	14320
37200052AL	IF600/65R28 CFO	160D	57	DW21B	58.5	23.9	176.4	40	9900
37200096AL	VF600/70R28 CFO	173D	71	DW21B	61.4	24.6	179.9	40	14300
37200054AL	VF600/60R30	147D	63	DW20B	58.7	23.2	170	40	6770
37200105AL	VF600/70R30 CFO	170D	70	DW21B	63	24.6	187.8	40	13200
37200063AL	VF620/75R30 CFO	169D	73	DW23B	65.9	25.6	191.1	40	12800
37200126AL	VF650/75R30 CFO	170D	74	DW20B	67.7	26	194.6	40	13900
37200136AL	VF800/65R32 CFO	184D	73	DW27B	72.6	30.5	213.2	40	19840
37200104AL	IF800/70R32 CFO	182A8	74	DW27B	76.1	30.9	224.6	25	18700
37200103AL	IF900/60R32 CFO	193D	73	DW30B	74.4	34.8	222.4	40	22000
37200150AL	IF1250/50R32 CFO	201B	76	DH44B	81.9	49.2	244.5	30	22480
37200097AL	IF650/65R34	161D	73	DW23	67.7	25.6	198.1	40	10200
37200031AL	IF520/85R38	167D	70	DW16L	77	21.3	230.9	40	12800
37200130AL	VF710/60R38	160D	68	DW25B	71.5	28	209.2	40	9910
37200141AL	VF710/70R38 CFO	178D	77	DW25B	77.1	28.3	225.1	40	16500
37200092AL	IF710/85R38 CFO	178D	84	DW25B	85.2	28.7	249.5	40	16500
37200118AL	IF800/70R38 CFO	187A8	79	DW27	81.9	32.3	240.2	25	21500
37200106AL	IF900/60R38	184A8	73	DW30B	80.1	34.6	236.7	30	19820
37200036AL	VF520/85R42 CFO	177A8	69	DW16L	77	21.3	230.9	30	16100
37200060AL	IF580/85R42	178D	72	DW20	80.3	23.4	238.8	40	16500
37200133AL	VF710/60R42	161D	68	DW25B	75.7	28	224	40	10190
37200095AL	VF 710/70R42 CFO	185D	79	DW25B	81.2	29.3	240.7	40	20400
37200180AL	VF710/75R42 CFO	181D	79	DW25B	84.8	28.5	247.2	40	18200

* Please note above load index refers to high speed (40MPH) loading capabilities. Visit ATG Tire website for lower speed loading details. Visit ATG Tire website for complete size availability

VISIT ATGTIRE.COM FOR DETAILED LOAD AND PRESSURE TABLES



Distributor:

ATG develops, manufactures and markets superior quality Off-Highway tires, globally, under three well known brands: Alliance, Galaxy and Primex. Specializing in Agriculture, Construction, Forestry, Industrial, Earthmoving, OEM and OTR application tires, the group is one of the fastest growing players in the Off-Highway tire market. ATG is dedicated to providing its customers with low Total Cost of Ownership (TCO) through superior products and exceptional customer support services.



Contact Alliance Tire Americas, Inc. at (800) 343-3276 or (781) 321-3910 for your nearest Alliance Tire Dealer.



facebook.com/alliancetireamericas



@alliancetireamericas



atablogs.atgtire.com



www.atgtire.com